



- A SEA WATER DRAIN POINT, 2x
- B SEA WATER INLET, CONNECTION FOR 63 mm (2 1/2") I.D. HOSE
- C1 WET EXHAUST BEND WITH RISER, OPTION 1
- C2 EXHAUST FLANGE, OPTION 2, MAX LOAD 9KG
- D FLEXIBLE SUSPENSION, STANDARD EQUIPMENT
- E1 OIL DIPSTICK AND FILLING ENGINE STARBOARD SIDE ALTERNATIVE
- E2 OIL DIPSTICK AND FILLING ENGINE PORT SIDE ALTERNATIVE
- F OUTLET FOR OIL BILGE PUMP (M8x1.5)
- G FRESH WATER FILLING (EXPANSION TANK)
- H FRESH WATER DRAIN POINT (3x)
- I OIL FILTER, 2x
- J BYPASS OIL FILTER
- K FUEL FILTER/WATER SEPARATOR
- L PRIMER PUMP
- M FUEL DEAIRATION
- N DIAGNOSIS CONNECTION (6-POLE)
- O CONNECTION SENDERS (6-POLE)
- P DATALINK CONNECTION (6-POLE)
- Q CONNECTION EVC (REVERSE GEAR)(32-POLE)
- R1 CONNECTION BATTERY POS.
- R2 CONNECTION BATTERY NEG
- S AIR FILTER
- T PRESSURE DROP INDICATOR, AIR FILTER
- U LIFTING EYE, 3x (Ø 30 MIN. FRONT EYE REMOVABLE)
- V HOSE CONNECTION HOT WATER OUTLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- W HOSE CONNECTION HOT WATER INLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- X FUEL CONNECTION INLET 1/4"-18 NPTF
- Y FUEL CONNECTION OUTLET 1/4"-18 NPTF
- Z PRESSURE LUBRICATION OF PROP SHAFT (1/4"-18NPTF)
- AA SEA WATER OUTLET FOR 2 1/8" I.D. HOSE (I.D. 54mm)
- AB EXTERNAL STOP CONNECTION
- AC CANZ CONNECTION
- AD AUTOMATIC FUSE, 10A (ENGINE)
- AE STOP BUTTON
- AF AUTOMATIC FUSE, 10A (EVC)
- AG OIL DIPSTICK AND FILLING TRANSMISSION
- AH OIL DRAIN TRANSMISSION
- AI EMERGENCY SHIFTING

SCALE 1:5	
WET WEIGHT 195KG (WITH OIL AND WATER)	
DRY WEIGHT 155KG (WITH OIL AND WATER)	
DIMENSIONS IN MILLIMETRE AND INCHES	
<small>For details, refer to the Volvo Penta website: www.volvo-penta.com</small> ENGINE DIMENSIONS D13B-B 90 HP REVERSE GEAR ZF 305-14E DIMENSION DRAWING For more information	21351700 05 1111